

CLAIMS

What is claimed is:

1. A method for controlling a start-up operation of a unit having at least a circuit portion and being connectable to an outside device, comprising the steps of:
 - executing a first self-checking test when a connection between the outside device and the circuit portion is not recognized; and
 - executing a second self-checking test including at least a part of said first self-checking test, when said connection between the outside device and the circuit portion is recognized.
2. The method according to Claim 1, wherein a predetermined command is transmitted from said unit to recognize said connection, and whether there is receipt of a control command output from said outside device in response to said predetermined command is detected.
3. The method according to Claim 2, wherein said predetermined command and said control command are communicated between said outside device and said circuit portion through an interface.
4. The method according to Claim 1, wherein said outside device is used for making a test or adjustment in a process of fabricating said unit.
5. The method according to Claim 1, wherein said outside device is used for making a test or adjustment in a process of analyzing a failure of said unit.

1 8. A control board, which is combined with a mechanical part for performing a
2 predetermined operation and stores a program for controlling said mechanical part,
3 comprising:

4 an interface for communicating data between said control board and an outside
5 device,

6 wherein said program includes one or more types of self-checking test programs,
7 and also includes a process of outputting a predetermined command to said outside
8 device through said interface and a process of selecting and executing a specific
9 self-checking test program from said one or more types of self-checking test programs
10 in accordance with a control command input from said outside device through said
11 interface in response to said predetermined command.

12 9. The control board according to Claim 8, wherein, at the time of selecting said
13 specific self-checking test program from said one or more types of self-checking test
14 programs, said specific self-checking test program is selected on the basis of whether a
15 predetermined flag has been set by a control command output from said outside device.

16 10. The control board according to Claim 9, wherein, when said flag has been set,
17 said specific self-checking test program is selected on the basis of a type of flag.

18 11. The control board according to Claim 8, further comprising an input-output port,
19 which is employed at a time of debugging a program, as said interface.

1 12. A device, comprising:
2 a mechanical part for performing a predetermined operation; and
3 a control section for controlling said mechanical part,
4 wherein said control section comprises:
5 a storage unit for storing one or more types of self-checking test programs which
6 are executed at a time of starting operation;
7 a notification unit for informing an outside device at a predetermined time that
8 a command is acceptable;
9 selection means for selecting a self-checking test program which is executed,
10 from among plural kinds of said self-checking test programs, based on whether or not
11 there is a control command input from said outside device in response to the notification
12 by said notification unit; and
13 an execution unit for executing said self-checking test programs selected by said
14 selection unit.

1 13. The device according to Claim 12, which is a tape drive unit for reading out or
2 writing data from or to a tape which is a storage medium.

1 14. A system for checking a product in a process of fabricating said product, the
2 system being equipped with a moving part and a control section for controlling said
3 moving part, wherein a command for shifting a checking process to a predetermined
4 self-checking test is output from said checking system connected to said product
5 fabricated to an extent having at least said control section, when said checking system
6 is notified by said product that a command is acceptable.

1 15. The checking system according to Claim 14, wherein the predetermined check
2 is made for said product given a predetermined self-checking test in response to said
3 command output from said checking system.

0000057-070601
T09040"4500660